

- · Front Suspension
- · Rear Suspension
- · Improved Brakes
- · No more bumps and unexpected slides
- · No more pothole panic
- · No more sore forearms and chipped teeth
- · Comfortable riding
- · Welcomes agressive racers

Unique Bushido Racing Bicycle Features

Front and rear tele-hydraulic suspension system with pneumatic springs and dampening levels adjustable for racer's weight and riding style.

Front suspension with 11½" of wheel travel and 3-way dampening adjustment (Soft, Stiff, and Locked).

Nono-shock rear suspension with 10" of wheel travel and infinite dampening adjustment (Soft to Locked). Hybrid monocoque aluminum swingarm and handlebar mounted dampening control.

Bushido Racing disc brakes have over three times the effective braking power of conventional brakes, while weighing much less. The alloy caliper weighs just 95 grams, and the composite disc (Kevlar and carbon-fiber) weighs less than 40 grams. The Bushido Racing disc brakes will also be available to fit, and retrofit old-fashioned conventional bicycles.

Bushido Racing hubs provide nearly indestructable wide-spaced flanges, non-bendable bolt-on or Q/R axles, sealed oversized bearings, and Bushido Racing disc brake drivers. The 100mm front hub weighs 150 grams. The 126mm rear hub with a Bushido Racing silent freewheel body weighs 280 grams. The standard freewheel body accepts all Suntour New Winner cogs. Shimano, Regina, and Zeus drivers are also available. The Bushido Racing hubs are available in all widths, and in all drillings.

The standard driveline configuation of the Bushido Racing Bicycle consists of either a 18 speed derailleur system, or a matainance-free Sturmey Archer 5 speed system. The Bushido Racing bicycle is available with other drivelines from fixed gear, to 21 speeds. All standard available components will fit the Bushido Racing Bicycle. The grafted brake, shift and suspension controles are standard Bushido Racing products. Bushido/Look racing pedals will be available in the future.

The standard 19½" frameset is constructed of TIG welded and normalized 4130 chrome-moly steel tubing. Titanium, aluminum, or oversized framesets are available on special order. The 445mm pneumatic seatpost will fit all riders up to 6'4", and is instantly adjustable for height. The Bushido Racing handlebars quickly adjust for desired angle and height (5" vertical). The frames are handfinished and coated with any available color.



